



AP GETOEL GL-4

MILD EP AUTOMOTIVE GEAR OILS

DESCRIPTION

AP GETOEL EP GL-4 are mild EP automotive gear oils meeting the performance requirements of API GL-4, MIL-L-2105B and CS 3000A. These oils are environmental friendly which contain neither lead nor chlorine. They exhibit good wear protection, anti-rust, anti-corrosion and excellent demulsification and foaming resistance properties.

BENEFITS

- Good oxidation and thermal stability
- Excellent rust and corrosion inhibition
- Good load-carrying capability

APPLICATION

AP GETOEL EP GL-4 are suitable for all gears in passenger cars and other automotive transmission systems operating under moderate conditions.

TYPICAL SPECIFICATION

SAE Grade		90	140	80W/90	85W/140
Kinematic Viscosity,					
@ 40°C, cSt	ASTM D445	196	460	157	425
@ 100°C, cSt	ASTM D445	18	30.5	16	30
Viscosity Index	ASTM D2270	96	95	101	97
Flash Point (COC), °C	ASTM D92	205	223	200	218
Pour Point, °C	ASTM D97	-10	-9	-25	-20

V. 072013



A.D. Sons Marine Tech

Hazi Ahmed Market
114 Sadarghat Road, Ctg.
Phone: +88 031 626116, Cell No: 01913 626187
E-mail: info@adsonsmarinetech.com
Website: www.adsonsmarinetech.com

Due to continuous research and development, the above typical data is subject to change without notice. The information should not be regarded as legally binding assurance of any properties or suitability for any particular application.